Ductware

LongNeck Bellmouth Spigots



Available in diameters of 150mm, 200mm, 250mm, 300mm, 350mm and 400mm.

Pre-punched holes allow for faster on-site installations.

Pre-installed gasket eliminates the need for sealants.

50mm offset enables insulation to fit between quadrant and duct wall.

Available with or without damper blade and quadrants.

Available with Rossi Everlock™ or Twistknob™ quadrant handles.

Ductware

Productivity solutions with green results

LongNeck Bellmouth Spigots

BASIC USE

Ductware's LongNeck Bellmouth Spigots are used to accommodate a circular duct take-off from rectangular ductwork.

The Bellmouth Spigot is usually fitted with a damper to control airflow, but is also available without damper & quadrant.

Bellmouth Spigots are an essential component when constructing aerodynamically superior duct.

FEATURES and BENEFITS

Ductware's LongNeck Bellmouth Spigots offer the following features and benefits:

A. 180mm deep drawn shell allows for a 50mm offset between quadrant and duct wall providing adequate space for external insulation.

B. A generous 90mm at the connection end allows for easier installation of flexible duct, with plenty of room to tape off and strap. This greatly reduces the time required for on-site flex duct installation.

C. Two roll grooved rings and fixing tabs around the top of the Spigot allows for the slight

variations in the inner core of flexible duct types. D. LongNeck Spigots are DEEP DRAWN, not spun, with the rolled top edge reducing the likelihood of on-site injury. E. Pre-punched holes for faster on-site and in-shop installation of Tek screws.

F. Pre-installed sticky based gasket eliminates the need to apply sealant resulting in reduced labour costs and a leak-resistant seal.

G. The spigot meets the Australian/New Zealand duct construction standards with a coating weight of 275grams.

LIMITED PRODUCT WARRANTY

Manufacturer is not liable for consequential, incidental or special damages. There are no statutory or implied warranties including the warranties of fitness for a particular purpose and merchantability. There are no warranties other than as set forth here and factory neither assumes nor authorises any person to assume any liability or other obligation in connection with LongNeck Bellmouth Spigots.

LongNeck Bellmouth Spigots are warranted to be free from any and all defects in material and workmanship only at the time of shipment from our factory. Manufacturer will at its sole option, replace or issue credit for the original purchase price. To determine the suitability of LongNeck Bellmouth Spigots for each specific purpose the user must conduct their own test.

Manufacturer does not guarantee the results from the use of LongNeck Bellmouth Spigots because of differences in application & fixing as well as the possibility of structural movement or externally

CODE	DESCRIPTION	UOM	Order Multiple
DW-SPG150D	LongNeck Bellmouth Spigot 150mm diameter	each	pallet / 200
DW-SPG150N	LongNeck Bellmouth Spigot 150mm diameter NO damper	each	pallet / 200
DW-SPG200D	LongNeck Bellmouth Spigot 200mm diameter	each	pallet / 128
DW-SPG200N	LongNeck Bellmouth Spigot 200mm diameter NO damper	each	pallet / 128
DW-SPG250D	LongNeck Bellmouth Spigot 250mm diameter	each	pallet / 72
DW-SPG250N	LongNeck Bellmouth Spigot 250mm diameter NO damper	each	pallet / 72
DW-SPG300D	LongNeck Bellmouth Spigot 300mm diameter	each	pallet / 72
DW-SPG300N	LongNeck Bellmouth Spigot 300m diameter NO damper	each	pallet / 72
DW-SPG350D	LongNeck Bellmouth Spigot 350mm diameter	each	tba
DW-SPG350N	LongNeck Bellmouth Spigot 350mm diameter NO damper	each	tba
DW-SPG400D	LongNeck Bellmouth Spigot 400mm diameter	each	tba
DW-SPG400N	LongNeck Bellmouth Spigot 400mm diameter NO damper	each	tba

Ductware

Productivity solutions with green results

AUSTRALIA: 1300 DUCTWARE(3828 9273)

www.ductware.com.au