

Ductware

Access Doors



Ductware®
Productivity solutions with green results

DESCRIPTION

Insulated access doors for HVAC plant equipment available in 5 stock sizes. Available in either outswing or inswing configuration. Custom special sizes also are available upon request.

TECHNICAL INFORMATION

HANDLES

- There are a variety of handle combinations depending upon your application.
- Choose between key locking, tool operated or non-locking.
- Both outswing and inswing handles have a built in, adjustable roller cam that enables positive engagement during the latching operation. The cam is normally placed on the right side of the handle, but can be moved to the left side.

All Ductware Access Doors are fitted inside with high visibility polyamide coated handles for safety. All handles are steel, zinc plated.

DOOR

Doors are constructed using 2 pieces of 1.2mm Galvanized sheet.

FRAME

Frame is formed from 3mm Galvanized steel.

INSULATION

50mm fibreglass insulation is hermetically sealed within the door.

DOOR SEAL

Heavy duty "fridge seal" is welded within door panel to ensure air tight seal.

HINGES

Unique flat-seal hinges ensure that the door closes flush with the frame and produces a positive, full engagement with the door seal.

SIZES

PRODUCT CODE	OPENING SIZE	DEPTH
DW-ADS	500 x 850mm	50mm
DW-ADM	520 x 1070mm	50mm
DW-ADL	520 x 1400mm	50mm
DW-ADXL	725 x 1400mm	50mm
DW-ADXXL	725 x 1635mm	50mm
DW-AD-SPEC	Custom special sizes to suit your application	50mm

Ductware
Productivity solutions with green results